



# Low-Temp Spray Wash

## Product Description

Low-Temp Spray Wash is a biodegradable, liquid cleaner designed to remove soil, oil and grease from iron, steel, aluminum and brass parts. It's suitable for use in spray wash cabinets, parts washers and soak tank applications and contains ingredients that inhibit corrosion and control foam.

### DILUTION INFORMATION

Light Soil: Mix 1 gallon of cleaner with 20 gallons of water  
 Heavy Soil: Mix 1 gallon of cleaner with 15 gallons of water

### APPLICATION

Heat the solution to 120°F (Min) to 150°F (Max). Product is designed to reduce foam at 120°F. Spray or soak parts to be cleaned. Let solution stand for 1 to 3 minutes depending on soil conditions. Dry parts with a blow or air dryer.

### SAFETY

Must read MSDS before using product. Use precautions when handling product. Always wear eye protection, gloves, apron and recommended personal protection. Always use product with proper ventilation.

## Specifications

Appearance	Clear	Odor	Slight solvent
pH (1% solution)	10.0 – 11.0	pH (undiluted)	12.2 12.7
Flash Point	>200°F	Weight	9.0 -9.2 lbs./gal
Biodegradable	Yes	Percent VOC's	< 5%
Solubility in water	Complete		

Available in bulk, 265 gallon tote, 55 gallon drum and 5 gallon pail

## Key Features

- Biodegradable
- Economical and effective at low concentrations
- Easy to use
- Foam controlled
- Low foam in hot water
- Use in hard or soft water