

Material Safety Data Sheet

Section 1 Product Identification

Product Name: **Transportation Cleaner**

Formula type: alkaline liquid detergent

Supplied By:

NOCO Lubricants
2440 Sheridan Drive
Tonawanda, NY 14150

Emergency Telephone: 1-800-424-9300
Information: 1-800-500-6626
Fax: 800-891-6626

Section 2 Chemical Ingredients

<u>Chemical Name</u>	<u>CAS#</u>	<u>%</u>	<u>Threshold Limit Value (TLV)</u>	<u>Permissible Exposure Limit (PEL)</u>
Water		75-85		
Detergent blend	proprietary	5-10	NE	NE
Potassium hydroxide	1310-58-3	0-3	TWA 2mg/m ³	
Dipropylene glycol methyl ether	34590-94-8	0-2	100 ppm (skin) OSHA	
Tetrasodium EDTA	64-02-8	1 - 5	none established	NDA

Section 3 Physical Data

Form:	Liquid	pH as is: 12.7 - 12.9
Color:	Pink	pH (1% vol): 9.9 - 10.4
Odor:	None	Solubility in Water: Complete
Specific Gravity (Water = 1):	1.062 - 1.067	Vapor Density (Air = 1): <1
Boiling Point °F: approx.	212	% VOC: <2
Evaporation Rate (Water = 1):	<1	Vapor pressure: similar to water

Section 4 Fire and Explosion Information

Flash Point (Method) F: Not flammable – product contains water

Unusual Fire and Explosion Hazards: Contact with metal can form hydrogen gas that is flammable and can form explosive mixtures with air. High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.

Extinguishing Agents: Foam, carbon dioxide, dry chemical, water fog, water

Fire fighting methods: General guidelines as this material won't burn without driving off water. Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible. Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of storage tank due to fire. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus with full face mask and full protective equipment.

Section 5 Health Hazard Data - Signs and Symptoms of Overexposure:

Probable Routes of Entry: Eyes, skin, inhalation

Eyes:	Direct contact will cause severe irritation and burns if not properly treated. Effects may range from mild to irreversible damage and blindness depending upon length of exposure, solution concentration and first aid measures.
Skin:	This product contains materials that can cause severe skin irritation. Prolonged or repeated contact may result in burns and irreversible damage. Prolonged exposure to diluted product can cause irritation.
Inhalation:	Overexposure by inhalation of misted product may lead irritation in respiratory tract, producing a burning, choking sensation. Caution should be taken to prevent atomizing or misting of this product without proper respiratory protection.

Ingestion: Ingestion is not expected to be a primary route of exposure. Do not ingest. Material will cause severe burns in mouth, throat and stomach. Note: Aspiration is a secondary hazard and should be expected. Product will attack lining of esophagus and stomach.

Section 6 Emergency First Aid Procedures

Eyes: Check for and remove contact lenses. Flush immediately with copious amounts of water for 15 minutes while holding eyelids apart to ensure complete irrigation of eye and eyelid tissues. Take exposed individual immediately to a health care professional, preferably an ophthalmologist, for emergency first aid and further evaluation.

Skin: Remove contaminated clothing. Immediately wash exposed area with copious amounts of water. Repeat washing. If redness or irritation occurs, seek immediate medical attention. Launder contaminated clothing before reuse.

Inhalation: If exposure by inhalation is suspected, immediately move exposed individual to fresh air. If individual experiences nausea, headache, dizziness, has difficulty breathing or is cyanotic, seek a health care professional immediately. Administer CPR if necessary.

Ingestion: Drink 1-2 large glasses of milk or water. Obtain immediate medical aid or call poison control. Do not induce vomiting unless directed by a physician. During vomiting there is a danger of aspirating liquid into lungs, causing serious damage and chemical pneumonitis. If spontaneous vomiting occurs, keep head below hips to prevent aspiration and monitor for breathing difficulty. Gastric lavage should be performed only by qualified medical personnel. Keep affected person warm and at rest. Seek immediate medical attention or call 911.

Section 7 Reactivity Data

Stability: Stable at room temperature (68F) when stored and used under proper conditions.

Incompatibility: Avoid contact with acids and oxidizing materials. Contact with metals can form flammable hydrogen gas.

Hazardous Decomposition Products: Smoke, carbon dioxide, carbon monoxide, oxides of nitrogen and sulfur, reactive hydrocarbons and irritating vapors.

Hazardous Polymerization: Will not occur.

Section 8 Spill & Leak Procedures

Procedures for Cleanup: Wear protective gear. Small spills: Mop thoroughly and rinse with water.

Large Spills: Evacuate area. Eliminate ignition sources. Block potential routes to water systems (sewers, streams, etc.) with inert material such as sand or dirt. Salvage for reuse if possible. Place into disposal containers. Wash down affected areas with clear water. RCRA regulated. Call local Emergency Response agency to report spill.

Waste Disposal: Contact the proper county, state or federal authorities. RCRA regulated.

Section 9 Special Protection Information

Ventilation Type Required: Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure.

Eye Protection: Eye protection must be worn. Wear safety glasses with side shields or vented splash proof goggles.

Protective Gloves: Impervious gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption.

Respiratory Protection: None required if airborne concentrations are maintained below threshold limits. Where misting and vapors may occur, wear an MSHA/NIOSH approved half mask form dust/mist air purifying respirator.

Other Equipment: Eyewash stations and showers should be available in areas where this material is used and stored. Rubber apron and boots.

Section 10 Special Precautions

Product should be stored between 40 and 95°F. Store out of direct sunlight. Keep out of reach of children. Keep container closed when not in use. For industrial and institutional use only. Mix only with water. Thoroughly rinse empty containers before disposal. Use only in well ventilated area. Do not breathe vapors. Wash hands thoroughly after handling.

Section 11 Toxicity Data

Carcinogenicity: NTP: No IARC: No OSHA: No

Section 12 Hazard Rating - HMIS

0 = minimal 1 = minimal 2 = moderate 3 = serious 4 = severe
 Health: 2 Reactivity: 0 Fire: 0 Personal protection equipment = B (gloves & glasses)

Section 13 Regulatory Information

Potassium hydroxide is subject to TSCA and SARA/Title III as an immediate health hazard.
 Dipropylene glycol methyl ether is subject to TSCA, SARA/Title III Sections 302, 304, 311, and 312

Section 14 Shipping Name:

Corrosive liquid, basic, inorganic, n.o.s. (potassium hydroxide), 8, UN3266, PGIII

Section 15 Documentary Information

Date issued: 3-8-2005 Supercedes: Reason for update:

ABBREVIATIONS: NE = NOT ESTABLISHED NDA = NO DATA AVAILABLE
 > = GREATER THAN <= LESS THAN

The data and recommendations presented herein are based upon our research and the research of others, and are believed to be accurate. However, no warranty of guarantee of their accuracy is made; and the products are distributed without any warranty, expressed or implied, including the limited warranties of merchantability of fitness for a particular purpose. The supplier makes no warranties, expressed or implied to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, adequacy or furnishing of such information. Employers should use this information only as a supplement to other information and must make independent determinations of suitability to assure proper use, safety, and health of employees.