



De-Scale/Rust Remove

Product Description

De-Scale/Rust Remove is a biodegradable, acidic liquid concentrate that's ideal for the removal of rust and scale on steel products. It contains a unique combination of ingredients for fast penetration and de-scaling action. This low foaming product is free of odor and fumes.

DILUTION INFORMATION

Mix 1 gallon of product with 4 to 9 gallons of water. Always add product to water.

APPLICATION

(Use protective clothing) Re-rusting after the de-rusting process can be prevented by not rinsing the treated parts. If rinsing is necessary, rinse with clean water, then rinse again with a diluted solution of De-Scale/Rust Remove and Wash. Cleaning Tank: Make sure tank is fiberglass, polyethylene, rubber lined or #316 steel.

- TEMPERATURE: Room Temperature up to 150°F.
- TIME: Normal standing time is 15 minutes 130°F. Adjust time for soil conditions and temperature.
- SURFACE RESULTS: Rust and scale removed. Normal finish is gray to black.

SAFETY

Note: Always wear protective equipment (goggles, gloves, rubber boots and apron) while using product. It contains phosphoric acid and can cause eye and skin burns. See MSDS for more precautions. Read MSDS before using product. Use precautions when handling products. Always wear eye protection, gloves, apron and recommended personal protection.

DISPOSAL & SPILLS

See MSDS Sheet. Always use product with proper ventilation.

Specifications

Appearance	Clear Green	Odor	Mild Acid
PH (1% solution)	0.5 -1.0	pH (undiluted)	1.5 – 2.5
Flash Point	None	Weight	9.7 – 10.0 lbs/gal
Biodegradable	Yes	Percent VOC's	None
Solubility in water	Complete		

Available in bulk, 55 gallon drum and 5 gallon pail

Key Features

- Biodegradable
- Low Foaming
- No odor or fumes
- Removes rust and scale on steel